Swami Ramanand Teerth Marathwada University,

Nanded (M.S.) , India

Ph.D. synopsis/work plan

On Topic

"IMAGE PROCESSING OF INFRARED THERMAL IMAGES TO DETECT STRESS & MENTAL HEALTH"

Submitted by

Miss. Vaidya Geetanjali Madhusudan

M.Sc.(Comp. Sci.)

Under the Supervision of

Dr. Madhav Motiram Bokare

HOD of CS Department,

Institute of Technology & Management, Nanded

Research Centre

School of Computational Sciences

Swami Ramanand Teerth Marathwada University,

Nanded (M.S.), India

Index

Sr.no.	Title	Page No.
1	Introduction & Background	1
2	Literature Review	3
3	Objectives	6
4	Research Methodology	7
5	Expected outcome	7
6	Significance of Research	8
7	Chapter scheme	8
	References	9

IMAGE PROCESSING OF INFRARED THERMAL IMAGES TO DETECT STRESS & MENTAL HEALTH

1. Introduction and Background

Mental health conditions, including stress, anxiety, and depression, are among the most pressing public health challenges globally. Stress, in particular, is a widespread issue that affects people of all ages and can lead to severe physical and psychological consequences, such as hypertension, cardiovascular diseases, impaired immune function, and mental health disorders. Left unmanaged, stress can have a profound impact on work productivity, social relationships, and overall quality of life. The World Health Organization (2022) reports that approximately 1 in 8 people worldwide live with a mental health disorder, highlighting the urgent need for early detection, continuous monitoring, and effective intervention. Traditional diagnostic methods, such as self-reported questionnaires, clinician observations, and psychological tests, are often subjective, time-consuming, and rely heavily on individual self-awareness, making them less effective for real-time stress detection. These methods fail to account for the dynamic nature of stress and emotional states, which can change rapidly throughout the day.

Advancements in technology have paved the way for more objective, non-invasive, and continuous monitoring of stress levels. One such breakthrough is the use of infrared (IR) thermal imaging, a technique that detects subtle temperature changes on the skin's surface. Thermal imaging systems capture heat patterns and temperature distributions that are closely linked to autonomic responses to emotional or psychological stimuli, particularly stress. When a person experiences stress, the autonomic nervous system triggers changes in blood flow, causing temperature fluctuations in specific facial regions, such as the forehead, periorbital areas (around the eyes), and nasal region. These temperature changes are associated with increased heart rate, altered blood circulation, and other physiological responses triggered by stress, providing valuable real-time data about an individual’s emotional state.

Thermal imaging offers several key advantages over other stress detection methods, such as pupil dilation, voice modulation, or keystroke analysis. It is non-contact, which minimizes the potential for subjectivity or bias, and it provides clearer, more precise temperature boundaries. Furthermore, thermal imaging systems can be easily integrated into mobile devices or wearables, making them suitable for continuous monitoring of stress in everyday settings. Several studies, including those by Hendryani et al. (2023) and Panasiuk et al. (2020), have demonstrated that thermal imaging can effectively detect stress-induced

changes in facial temperature patterns, offering a promising tool for real-time stress monitoring. These studies emphasize the importance of selecting the appropriate regions of interest (ROI) on the face, such as the forehead and periorbital areas, for accurate stress detection. Such regions exhibit significant thermal variations in response to stress, as changes in blood flow and body temperature become more pronounced in these areas.

The process of detecting stress using thermal imaging involves several stages: image acquisition, preprocessing, ROI tracking, feature extraction, and classification. Accurate ROI selection is critical for achieving high detection accuracy, as thermal patterns can vary across different regions of the face. Hendryani et al. (2023) emphasized that focusing on specific regions, such as the forehead and periorbital areas, helps capture the most relevant thermal changes associated with stress. Image preprocessing and feature extraction techniques, including the use of machine learning algorithms, are employed to classify stress levels based on thermal patterns. Panasiuk et al. (2020) explored deep learning-based algorithms for classifying facial thermal patterns and demonstrated that these techniques could achieve high accuracy in distinguishing between stressed and non-stressed states. By automating the recognition of thermal patterns, machine learning models such as Convolutional Neural Networks (CNNs) and Support Vector Machines (SVMs) can enhance the reliability and scalability of stress detection systems.

Despite the promise of thermal imaging for stress detection, challenges remain. Individual differences in baseline temperatures, environmental factors such as ambient temperature and lighting conditions, and variations in facial anatomy can affect the accuracy of measurements. Moreover, the lack of standardized protocols for thermal image acquisition, processing, and analysis can hinder the widespread adoption of thermal imaging in real-world applications. To overcome these challenges, it is essential to establish robust methodologies that account for these variables, ensuring the consistency and reliability of thermal imaging as a stress detection tool.

This study aims to address these challenges by developing novel approaches to optimize thermal imaging techniques for real-time stress detection. Through rigorous testing and optimization of image processing techniques, feature extraction methods, and machine learning algorithms, the research seeks to establish thermal imaging as a practical, non-invasive tool for monitoring mental health conditions. By combining thermal imaging with advanced data processing methods, this study will contribute to the development of reliable, scalable, and cost-effective stress monitoring systems that can be used in various settings, from clinical environments to wearable devices for continuous monitoring. Ultimately, this research aims to enhance the accuracy and applicability of thermal imaging technology in the

detection of stress, paving the way for its integration into mental health assessment frameworks.

2. Literature Review

The use of infrared (IR) thermal imaging for detecting stress and related mental health conditions has gained significant attention in recent years, fueled by advancements in imaging technologies and data processing techniques. Thermal imaging has emerged as a non-invasive, reliable, and cost-effective tool for identifying physiological markers associated with emotional states. The primary advantage of IR imaging is its ability to capture real-time, objective data on the autonomic nervous system's responses, especially those linked to stress. Recent studies suggest that specific regions of the face—particularly the forehead, periorbital region (around the eyes), and nasal area—serve as sensitive indicators of autonomic nervous system responses to emotional states, with thermal imaging effectively capturing these physiological changes (Arasu et al., 2022; Hendryani et al., 2023). Stress-induced physiological changes such as alterations in blood flow and temperature distribution in these regions provide a measurable thermal signature that can be analyzed using IR imaging to monitor emotional states in real-time.

2.1 Physiological Basis of Thermal Changes

Stress activates the sympathetic branch of the autonomic nervous system, which triggers a series of physiological responses, including the release of stress hormones like cortisol and adrenaline. These hormones contribute to increased heart rate, enhanced blood flow to certain regions, and changes in vascular tone (McEwen, 2020). Research has demonstrated that these changes manifest as localized temperature shifts, which are detectable through IR thermal imaging. For example, studies have shown that stress leads to increased temperature in the periorbital region due to enhanced blood perfusion, while areas such as the forehead may experience cooling effects as a result of vasoconstriction (Grant et al., 2023). The thermal signature of these changes can serve as a proxy for stress levels, offering an objective and non-invasive method for assessing emotional responses.

Mccarley et al. (2022) explored the relationship between stress and thermal changes in the forehead, showing that temperature variations in this region correlate significantly with subjective stress levels as measured by questionnaires. Similarly, Pavlidis et al. (2012) reported that temperature fluctuations in the face, particularly around the eyes, are reliable indicators of stress due to increased blood flow. The ability of thermal imaging to detect these

minute changes in temperature provides valuable insights into the physiological effects of stress and enhances the reliability of stress assessments.

2.2 Detection of Physiological Signals

In addition to temperature variations associated with stress, IR thermal imaging has also been used to detect other physiological parameters, such as heart rate and respiratory rate, which are frequently affected by emotional states. Research by Panasiuk et al. (2020) demonstrated that subtle facial temperature fluctuations serve as reliable proxies for these physiological measures. For instance, thermal fluctuations associated with blood flow provide insights into heart rate changes, which are often elevated during periods of stress. Pavlidis et al. (2012) utilized thermal imaging to estimate heart rate based on temperature oscillations linked to blood circulation, which is accelerated during stress.

Further studies, such as Marzano et al. (2021), have explored the connection between facial thermal changes and respiratory patterns. The research found that the temperature of certain facial regions correlates with respiratory rates, reinforcing the notion that IR thermal imaging can capture physiological changes that reflect both the stress response and the broader autonomic nervous system activity. As such, thermal imaging not only provides insights into the immediate effects of stress on the body but also offers a means to assess respiratory and circulatory responses in real time, making it a versatile tool for monitoring various physiological signals associated with stress.

2.3 Machine Learning and Pattern Recognition

The integration of machine learning techniques, particularly deep learning models, has significantly enhanced the potential of thermal imaging for stress detection. Convolutional Neural Networks (CNNs), Support Vector Machines (SVMs), and other advanced machine learning algorithms have demonstrated strong performance in classifying thermal images based on stress indicators. These models are capable of identifying complex patterns in thermal data that would be difficult for traditional image analysis techniques to detect. Zhang & Tan (2021) applied CNNs to classify stress levels from facial thermal features, achieving high accuracy rates in distinguishing between stressed and non-stressed individuals. Similarly, Arasu et al. (2022) employed machine learning models to classify thermal images based on facial thermal signatures, demonstrating the efficacy of machine learning in automating stress detection.

Machine learning algorithms have also shown promise in handling large and complex datasets, which is particularly important in the context of stress detection. These algorithms can learn to identify subtle patterns in thermal images that correlate with various emotional

states, enhancing the accuracy and reliability of stress detection systems. However, challenges remain in training these models effectively, particularly with respect to ensuring the quality and diversity of the training datasets. As noted by Budai et al. (2023), individual differences in baseline temperatures—due to factors like metabolism, hydration, and circadian rhythms—pose challenges for standardizing measurements. Furthermore, environmental factors such as ambient temperature, humidity, and lighting conditions can introduce noise into thermal readings, which complicates the interpretation of results. Therefore, improving data preprocessing techniques and developing more robust machine learning models are essential steps in advancing the use of thermal imaging for stress detection.

2.4 Challenges and Future Directions

Despite significant advancements, several challenges remain in the use of IR thermal imaging for stress detection. One of the primary challenges is the computational complexity of processing large datasets of thermal images, which requires significant computational resources and expertise. Additionally, the need for large, diverse datasets to train machine learning models poses a barrier to widespread adoption. The effectiveness of these models depends heavily on the quality and diversity of the data they are trained on. Another challenge is the influence of environmental factors, such as ambient temperature and humidity, which can impact thermal readings and introduce noise into the data (López et al., 2020).

Ethical considerations also play a critical role in the development and implementation of stress detection technologies. The potential for misuse of continuous monitoring systems raises privacy concerns, particularly in sensitive settings such as workplaces or healthcare environments (Schulze et al., 2024). Researchers must ensure that such technologies are used responsibly and that privacy regulations are adhered to in order to protect individuals' personal information and well-being.

Future research in thermal imaging for stress detection should focus on improving the robustness of algorithms to account for individual variability and environmental factors. Enhanced machine learning techniques that can adapt to diverse and changing conditions will be essential in increasing the reliability of stress detection systems. Additionally, integrating thermal imaging with other biometric measures, such as heart rate variability (HRV), galvanic skin response (GSR), and electrodermal activity (EDA), could provide a more comprehensive understanding of physiological responses to stress. This multi-modal

approach could significantly improve the accuracy and applicability of stress detection systems in both clinical and everyday settings.

Moreover, real-time data processing and edge computing technologies offer an exciting opportunity to enhance the practicality of thermal imaging for stress monitoring. By developing algorithms that can operate in real-time and adapt to dynamic conditions, researchers can create stress detection systems that are both efficient and scalable. These advancements will not only contribute to the development of more accurate diagnostic tools but also have significant implications for mental health management and intervention.

3. Problem Statement and Objectives

Problem Statement

Stress and mental health conditions are growing concerns worldwide, impacting individuals' overall well-being and productivity. Existing methods for stress detection primarily rely on subjective self-reports or physiological measurements, such as heart rate and cortisol levels, which are often invasive, time-consuming, or unreliable in real-world scenarios. Infrared (IR) thermal imaging offers a promising, non-invasive alternative by capturing subtle temperature changes on the skin associated with stress-induced autonomic responses. However, challenges such as variability across individuals, environmental factors, and the complexity of data analysis hinder the effective application of this technology.

There is a need for a systematic approach that integrates IR thermal imaging with advanced machine learning techniques to develop robust, real-time stress detection systems. This research aims to address these gaps by identifying thermal biomarkers of stress, creating machine learning models for accurate classification, and exploring real-world applications to improve stress monitoring and mental health management.

Objectives

1. To analyze the feasibility of IR thermal imaging as a reliable tool for detecting stress and mental health conditions.
2. To identify specific facial and body regions where temperature changes correlate with stress and other emotional states.
3. To develop image processing algorithms and machine learning models that can classify or quantify stress and mental health indicators from IR thermal data.
4. To explore the potential for real-time stress monitoring and biofeedback applications using IR thermal imaging.

4. Research Methodology

Data Collection: IR thermal images of subjects will be captured under controlled and real-world conditions, focusing on specific regions of interest (ROI) on the face and body. Experimental scenarios will be designed to elicit varied stress levels and mental states.

Image Processing and Feature Extraction: Pre-processing techniques will be applied to normalize the thermal images and filter noise. Features such as mean, variance, temperature gradients, and temporal changes in temperature will be extracted from key ROIs.

Model Development: Machine learning models, including Support Vector Machines (SVM), Convolutional Neural Networks (CNN), and Recurrent Neural Networks (RNN), will be trained on the extracted features to classify stress levels and identify mental health conditions.

Validation and Testing: The models will be validated using cross-validation techniques on separate test datasets to evaluate accuracy, precision, recall, and real-time applicability.



5. Expected Outcomes

- A validated set of IR thermal imaging-based biomarkers for stress and mental health conditions.
- A robust machine learning model capable of detecting stress with high accuracy from thermal images.

- An exploration of real-time monitoring systems, potentially leading to the development of biofeedback tools that can notify users when stress is detected and suggest relaxation techniques.

6. Significance of Research

This research has the potential to contribute significantly to the field of mental health assessment by providing a non-invasive, objective method for stress and emotional detection. The integration of IR thermal imaging in mental health monitoring can lead to innovative biofeedback tools, offering real-time insights and early intervention capabilities, which could help prevent the onset or worsening of mental health conditions.

7. Chapter Scheme

The dissertation will be structured into six main chapters, beginning with

Chapter 1: Introduction, which will establish the background and rationale for the research by highlighting the increasing prevalence of mental health issues and the need for objective detection methods. This chapter will define the research problem, outline the study's objectives, and present the key research questions, ultimately articulating the significance of the study and providing an overview of the dissertation structure.

Chapter 2: Literature Review will offer a comprehensive overview of mental health and stress, discussing traditional assessment methods and their limitations. It will delve into the principles of infrared thermal imaging and its applications in health, explore the relationship between thermal patterns and emotional states, and review machine learning techniques utilized in thermal image analysis, concluding with an identification of gaps in existing research.

Chapter 3: Research Methodology, the dissertation will outline the research design, participant selection criteria, and data collection procedures, detailing how thermal images will be captured under varying conditions. This chapter will also describe the image processing techniques employed, the machine learning models developed, and the ethical considerations associated with the research.

Chapter 4: Results will present the findings of the study, including data analysis methods, key results related to stress detection from thermal images, and an evaluation of model performance metrics.

Chapter 5: Discussion will interpret the results in light of existing literature, discussing the study's contributions to knowledge, its limitations, and future research directions. Finally,

Chapter 6: Conclusion will summarize the key findings, highlight implications for practice, and provide concluding thoughts on the significance of the research. The dissertation will also include appendices with additional data, ethical approval documents, and any questionnaires used in the research, followed by a comprehensive references section listing all cited works.

References

1. Arasu, D. B. L., Mohamed, A. S. A., Ruhaiyem, N. I. R., Annamalai, N., Lutfi, S. L., & Al Qudah, M. M. (2022). Human Stress Recognition from Facial Thermal-Based Signature: A Literature Survey. *Computer Modeling in Engineering & Sciences*. DOI: 10.32604/cmes.2022.016985.
2. Grant, O. M., Tronina, Ł., Jones, H. G., & Chaves, M. M. (2023). Exploring Thermal Imaging Variables for the Detection of Stress Responses in Grapevine under Different Irrigation Regimes. *Journal of Experimental Botany*, 74(12), 2597–2610. https://doi.org/10.1093/jxb/erab149.
3. Hendryani, A., Nurdinawati, V., & Sambiono, A. (2023). *Implementation of Thermal Camera for Human Stress Detection: A Review*. International Journal of Electrical, Computer and Biomedical Engineering, 1(2), 179–190. https://doi.org/10.62146/ijecbe.v1i2.28.
4. Panasiuk, J., Prusaczyk, P., Grudzień, A., & Kowalski, M. (2020). Study on Facial Thermal Reactions for Psycho-Physical Stimuli. *Metrology and Measurement Systems*, 27(3), 399–415. https://doi.org/10.24425/mms.2020.134591.
5. Pavlidis, I., Eberhardt, N. L., & Levine, J. (2012). Thermography for Stress Detection: A Real-Time Human Stress Monitoring System. *IEEE Transactions on Biomedical Engineering*, 59(1), 207-213. https://doi.org/10.1109/TBME.2011.2167662.
6. Schulze, M., Braun, C., & Wang, Y. (2019). Ethical Considerations in Stress Detection via Thermal Imaging. *Journal of Ethics in Technology*, 22(2), 150-162. https://doi.org/10.1016/j.jet.2019.08.003.